



Shaft Trim Specifications

Pattern	Tip x Butt Dia.		Length	Weight	Flex						Price
2006 Accumade Shafts											
BL - Iron											
Stepped	.370 x .600		41	125	R/S						\$ 7.75
R Flex Trim											
Iron	1	2	3	4	5	6	7	8	9	PW	
Trim	0	.5	1.0	1.5	2.0	2.5	3.0	3.5	4.0	4.5	
S Flex Trim											
Iron	1	2	3	4	5	6	7	8	9	PW	
Trim	.5	1.0	1.5	2.0	2.5	3.0	3.5	4.0	4.5	5.0	
BL - Wood											
Stepped	.335 x .590		46	135	R/S						\$ 9.50
R Flex Trim											
Wood	1	2	3	4	5	7	9				
Trim	0	.25	.5	.75	1.0	1.5	2.0				
S Flex Trim											
Wood	1	2	3	4	5	7	9				
Trim	2	2.25	2.5	2.75	3.0	3.50	4.0				
BSL - Iron											
Stepless	.370 x .600		41	124	R/S						\$ 9.75
R Flex Trim											
Iron	1	2	3	4	5	6	7	8	9	PW	
Trim	0	.5	1.0	1.5	2.0	2.5	3.0	3.5	4.0	4.5	
S Flex Trim											
Iron	1	2	3	4	5	6	7	8	9	PW	
Trim	.5	1.0	1.5	2.0	2.5	3.0	3.5	4.0	4.5	5.0	
BSL - Wood											
Stepless	.335 x .590		46	135	R/S						\$ 11.00
R Flex Trim											
Wood	1	2	3	4	5	7	9				
Trim	0	.25	.5	.75	1.0	1.5	2.0				
S Flex Trim											
Wood	1	2	3	4	5	7	9				
Trim	2	2.25	2.5	2.75	3.0	3.50	4.0				
SL - Iron											
Stepped	.370 x .570		39	120	A/L						\$ 7.25
A Flex Trim											
Iron	1	2	3	4	5	6	7	8	9	PW	
Trim	0	.5	1.0	1.5	2.0	2.5	3.0	3.5	4.0	4.5	
L Flex Trim											
Iron	1	2	3	4	5	6	7	8	9	PW	
Trim	.5	1.0	1.5	2.0	2.5	3.0	3.5	4.0	4.5	5.0	